

INFINITY® PRELUDE® FORTY

3-1/2 way Floorstanding Loudspeaker

 **Infinity**®

TECHNOLOGY • PERFORMANCE • DESIGN



HIGHLIGHTS

- Represents a refinement of the principles that have guided Infinity® loudspeaker designs for more than 40 years.
- Dual 8" CMMD® woofers, four patent-pending Maximum Radiating Surface™ (MRS™) mid-bass/midrange drivers and an all-new 1" CMMD high-frequency driver configuration.
- Impressive cabinet design and meticulously crafted enclosures.
- Sophisticated crossover network with premium-grade capacitors and inductors.
- Available in real-wood cherry and high-gloss black.

ADVANCING THE LEGEND

Infinity introduced the Prelude name more than a decade ago, proudly applying it to some of the most critically-acclaimed and fondly-remembered systems in our history. With an array of CMMD drivers that includes a four-driver array of midrange speakers, dual side-firing woofers, and a 1-inch dome tweeter, the new Prelude Forty owes a clear design debt to Prelude systems that have gone before. But with MRS driver technology for exceptionally flat, broadband frequency response and uniform on- and offaxis dispersion, Prelude Forty achieves a level of sonic realism all its own, with warmth that can reveal the soul of any musical performance.

KEY SPECIFICATIONS

- The Prelude Forty features dual 200mm side-firing CMMD woofers, for sound that is extravagantly full, deep and clean, under any listening conditions, with intensely realistic bass response
- Employs second-generation Maximum Radiating Surface™ (MRS) flat-panel transducers
- A fast, lightweight, newly designed 25mm CMMD-dome tweeter extends the high-frequency driver's response and delivers cleaner, more realistic high-frequency sound
- Sophisticated crossover network with premium-grade capacitors and inductors minimizes colorations for more lifelike reproduction across the audio spectrum
- Prelude Forty enclosures are meticulously crafted in a choice of high-gloss black or real cherry finish
- Dual 200mm CMMD®, cast-frame, magnetically shielded Low-Frequency Drivers
- Dual MRS™ CMMD®, magnetically shielded Mid-Bass Drivers
- Dual MRS™ CMMD®, magnetically shielded Mid-Range Drivers
- 25mm CMMD®, magnetically shielded High-Frequency Driver

INFINITY® PRELUDE® FORTY

3-1/2 way Floorstanding Loudspeaker



SPECIFICATIONS

- Frequency Response: 42Hz–40kHz (± 3 dB); 36kHz (-6 dB)
- Recommended Amplifier Power Range: 50–250 Watts
- Sensitivity: 85dB (2.83V @ 1 meter)
- Nominal Impedance: 8 Ohms
- Low-Frequency Drivers: Dual 200mm (8") CMMD®, cast-frame, magnetically shielded
- Mid-Bass Drivers: Dual 197mm x 85mm MRS™ (7-3/4" x 3-3/8") CMMD®, magnetically shielded
- Mid-Range Drivers: Dual 197mm x 85mm MRS™ (7-3/4" x 3-3/8") CMMD®, magnetically shielded
- High-Frequency Driver: 25mm (1") CMMD®, magnetically shielded
- Dimensions – excluding feet (H x W x D): 1452mm x 178mm x 470mm
- Dimensions – including feet (H x W x D): 1452mm x 391mm x 470mm
- Weight: 37.3kg (82 lb)



Bindings



Feet

Harman Consumer Group, Inc.
8500 Balboa Boulevard, Northridge, CA 91329 USA

www.infinitysystems.com

H A Harman International Company

© 2008 Harman International Industries, Incorporated. All rights reserved. Infinity and CMMD are trademarks of Harman International Industries, Incorporated, registered in the United States and/or other countries. Maximum Radiating Surface (MRS) is a trademark of Harman International Industries, Incorporated.

Features, specifications and appearance are subject to change without notice.