Control Series

CM40, CM42, CM52, CM62, CONTROL1X, CONTROL1G Universe, CONTROL MEDIA



Control Media (active version)

- Ultra-compact monitors
- Rugged, molded cabinets
- Laminate dome tweeters

- Poly-Laminate bass/midrange driver cones
- Magnetic shielding for video applications
- Integral fittings for optional wall brackets



Control Series

CM40, CM42, CM52, CM62, CONTROL1X, CONTROL1G Universe, CONTROL MEDIA

Designed for balanced all-round system performance in locations where space is at a premium, the ultracompact JBL Control Series represents outstanding value for money and exceptional flexibility of use and placement. Titanium dome tweeters and bass/midrange drivers with specially developed Poly-Laminate cones deliver full-range, full-bodied performance from an attractive compact package. The custom designed drivers are framed in attractive blue trim rings.

Rugged, Durable Enclosures

The distinctive molded Control compact monitor cabinets with stylishly rounded edges are available in black or white with matching removeable grilles. The JBL badge rotates to match the orientation of the speaker. Selected models are also available in special all-weather versions for outdoor use.

Wall-Mounting Accessories

Each Control Series monitor is pre-mounted with integral fittings which mate with separate optional brackets for firm, reliable wall-mounting. The brackets are available in black or white to match the Control Series monitors



Specifications	CM 40	CM 42	CM 52
Drivers:	4" full-range	4" bass/midrange	5 1/4" bass/midrange
Drivers tweeter:	-	1/2" Titanium dome	3/4" Titanium dome
Frequency response:	70 Hz - 16 kHz	60 Hz - 20 kHz	50 Hz - 20 kHz
Power handling:	75 Watts	80 Watts	100 Watts
Sensitivity:	87 dB	88 dB	89 dB
Nominal impedance:	6 Ohms	6 Ohms	6 Ohms
Dimensions (HxWxD):	225x147x104 mm	225x147x104 mm	265x171x168 mm
Finish:	Black or White	Black or White	Black or White

CM 62	Control 1G Universe/1X	Control Media
6 1/2"	5 1/4" (Video shielded)	5 1/4"
3/4" Titanium dome	1/2" Titanium dome (Video shielded)	1/2" Titanium dome
45 Hz - 20 kHz	70 Hz - 20 kHz	70 Hz - 20 kHz
175 Watts	125 Watts	-
-	:-	2x20 Watts
89 dB	87db	87db
6 Ohms	4 Ohms	4 Ohms
390x243x262 mm	230x155x140 mm	230x155x140 mm
Black or White	Black or White	Black, White or computer Grey
	6 1/2" 3/4" Titanium dome 45 Hz - 20 kHz 175 Watts - 89 dB 6 Ohms 390x243x262 mm	6 1/2" 5 1/4" (Video shielded) 3/4" Titanium dome 1/2" Titanium dome (Video shielded) 45 Hz - 20 kHz 70 Hz - 20 kHz 175 Watts 125 Watts 89 dB 87db 6 Ohms 4 Ohms 390x243x262 mm 230x155x140 mm

JBL continually strives to update and improve existing product, as well as create new ones. The specifications and constructions details in this and related JBL publications are therefore subject to change without prior notice.

