

# Project Array™ – 800 Array

High-performance loudspeaker



To deliver extraordinary sonic performance in the finest home theater and music systems, JBL® Project Array™ models utilize technologies directly derived from the company's flagship K2® Series loudspeakers and professional recording studio monitors. Project Array models include the 1400 Array, 1000 Array and 800 Array floorstanding and bookshelf loudspeakers; the 880 Array center channel loudspeaker; and the 1500 Array powered subwoofer with built-in 1000-watt amplifier. To achieve its superlative performance, the 800 Array loudspeaker features newly designed Bi-Radial®-horn compression drivers mounted vertically in a freestanding configuration. This design eliminates enclosure diffraction effects to provide precise, ultra-stable imaging, along with a wider, deeper, more three-dimensional soundstage.

## Highlights

- Aluminum compression driver
- Titanium tweeter
- Classic JBL professional bass driver
- Unique enclosure
- Seamless system integration

## Key Specifications

- Description: Three-way, 200mm (8") bookshelf speaker
- Frequency response: 55Hz – 40kHz
- Crossover frequencies: 1000Hz/8kHz
- Power handling: 200 Watts
- Sensitivity (2.83V@1m): 88dB
- Nominal impedance: 8 Ohms
- Dimensions (H x W x D): 743mm x 273mm x 356mm (29-1/4" x 10-3/4" x 14")
- Weight: 18kg (40 lb)

# Project Array™ – 800 Array

High-performance loudspeaker



## Features

- Three-way floorstanding bookshelf design featuring:
  - A 200mm (8") polymer-treated pulp-cone low-frequency driver with 38mm (1-1/2") copper voice coils wound on an aluminum former.
  - A 045Ti 25mm (1") pure-titanium ultrahigh-frequency compression driver.
  - A 175Nd-3 44mm (1-3/4") Aquaplas-treated aluminum-dome high-frequency compression driver.
- Utilizes a vertically oriented, enclosure-less Bi-Radial-horn configuration to provide spacious, dynamic and natural sound quality.
- Incorporates a high-performance JBL 175Nd high-frequency compression driver with an aluminum edge-wound voice coil, neodymium motor assembly and Aquaplas-treated aluminum dome, mated to a rapid-flare phase plug and the Bi-Radial-horn assembly.
- 015M transducer features a 22mm (0.88") Mylar® diaphragm, directly mounted to the top of the Bi-Radial horn. To achieve tight, musically natural bass response, the 800 Array uses a 200mm (8") polymer-treated pulp-cone woofer.
- Built to the same uncompromising quality and construction standards as every Project Array model, the 800 Array is equally adept at movie soundtrack and music reproduction, with a smooth tonal balance; transparent, musically inviting midrange; and open, extended high frequencies.

Harman Consumer Group, Inc.

2, route de Tours, 72500 Château du Loir, France • 250 Crossways Park Drive, Woodbury, NY 11797, USA • 8500 Balboa Boulevard, Northridge, CA 91329, USA

[www.jbl.com](http://www.jbl.com)

**H** A Harman International Company

© 2007 Harman International Industries, Incorporated. All rights reserved. JBL, Bi-Radial and K2 are trademarks of Harman International Industries, Incorporated, registered in the United States and/or other countries. Project Array is a trademark of Harman International Industries, Incorporated. Mylar is a registered trademark of E.I. du Pont de Nemours and Company.

Features, specifications and appearance are subject to change without notice.