



# CUSTOMER SERVICE DEPARTMENT

## HIGH FREQUENCY DIRECT RADIATOR TEST SPECIFICATIONS

Revision D - Effective January 16, 1984

Page 1 of 2

Replaces Revision C (July 5, 1983)

MODEL	TYPE	DIAPHRAGM MATERIAL	MAGNET TYPE	NOM IMP SL	DYNAMIC TEST		DC RESISTANCE MINIMUM-MAXIMUM	NOTES
					INPUT V	SWEEP FREQ HZ		
010	1" Dome	Cloth	Ferrite	4	3	2K-12K	2.4 - 2.9	
011	1" Dome	Cloth	Ferrite	4	3	2K-12K	2.7 - 3.3	
024	1" Dome	Phenolic	Ferrite	8	5	200-1200	3.5 - 4.5	
033	1" Dome	Phenolic	Ferrite	8	5*	200-1200	3.6 - 4.4	*Test with network
034	1" Dome	Phenolic	Ferrite	8	2.5*	200-2000	5.4 - 6.6	*Test with network
044	1" Dome	Phenolic	Ferrite	8	2	2K-12K	5.4 - 6.6	
044-1	1" Dome	Phenolic	Ferrite	8	2	2K-12K	5.4 - 6.6	Gold dome, black flange
066	1" Dome	Phenolic	Ferrite	8	5*	200-1200	3.5 - 4.4	*Test with network
LE20	1 3/4" Cone	Paper	Alnico	8	6*	1K-6K	3.7 - 4.2	*Test with network with dust screen
LE20-1	1 3/4" Cone	Paper	Alnico	8	6*	1K-6K	3.7 - 4.2	*Test with network
LE21H	1 3/4" Cone	Paper	Ferrite	8	3	500-1200	3.7 - 4.2	Has binding posts
LE25	1 3/4" Cone	Paper	Ferrite	8	3	500-1200	3.7 - 4.2	
LE25-1	1 3/4" Cone	Paper	Ferrite	8	3	500-1200	3.7 - 4.2	
LE25-2	1 3/4" Cone	Paper	Ferrite	8	3	500-1200	3.6 - 4.4	
LE25-3	1 3/4" Cone	Paper	Ferrite	8	3	500-1200	3.7 - 4.2	
LE25-4	1 3/4" Cone	Paper	Ferrite	8	3	500-1200	3.7 - 4.2	
LE25-5	1 3/4" Cone	Paper	Ferrite	8	3	500-1200	3.7 - 4.2	



# CUSTOMER SERVICE DEPARTMENT

## HIGH FREQUENCY DIRECT RADIATOR TEST SPECIFICATIONS

Revision D - Effective January 16, 1984  
Replaces Revision C (July 5, 1983)

Page 2 of 2

MODEL	TYPE	DIAPHRAGM MATERIAL	MAGNET TYPE	NOM IMP SL	DYNAMIC TEST		DC RESISTANCE MINIMUM-MAXIMUM	NOTES
					INPUT V	SWEEP FREQ HZ		
LE26	1 3/4" Cone	Paper	Ferrite	8	3	500-1200	3.4 - 4.3	Plastic flange
LE30	3" Dome	Aluminum	Alnico	8	3	350-1200	5.4 - 6.6	
401-132	1 3/4" Cone	Paper	Alnico	8	6*	1K-3K	3.7 - 4.2	*Test with network, OEM
303G	2" Cone	Plastic	Ferrite	8	4*	1K-2K	3.6 - 4.4	*Test with network
303G-1	2" Cone	Paper	Ferrite	8	4*	1K-2K	3.6 - 4.4	*Test with network
303G-2	2" Cone	Paper	Ferrite	8	4*	1K-2K	3.6 - 4.4	*Test with network