



## SPECIFICATIONS

### [POWER SUPPLY SECTION]

<b>Power Requirement</b>	: AC 120V ± 10% or 220V ± 10% (K.W TYPE) AC 240V ± 10% or 220V ± 10% (T TYPE) 50 ~ 60 Hz
<b>Power Consumption</b>	: Less than 90W
<b>Output Voltage</b>	: DC 13.8V
<b>Output Current</b>	: Intermittent 3.5A Continuous 2A
<b>Fluctuation</b>	: Less than ± 4% (against an input AC voltage variation of 220V or 240V ± 10%)
<b>Ripple Component</b>	: Less than 10mV (r.m.s) (at 3.5A output current, AC 220V or 240V ± 10%)
<b>Protection Circuit</b>	: Operating Point at output current 4.5 A
<b>Operating temperature</b>	: -10°C ~ +50°C (14°F ~ 122°F)
<b>Dimensions</b>	: 152 (6) wide × 90 (3-9/16) high × 214 (8-7/16) deep mm (inch)
<b>Weight</b>	: 02About 3.2 kg (7.1 lbs.)

### [SPEAKER SECTION]

<b>Rated input</b>	: 1 W
<b>Impedance</b>	: 8 ohms
<b>Size</b>	: 77mm dia.
<b>Frequency response</b>	: 200 – 3500 Hz

The above specifications are subject to change without notice for further improvement.

### Accessories supplied

Operating manual	1 piece
DC power cord with plug	1 piece
Fuse (1A)	1 piece
	(2A) 1 piece (K.W TYPE)
Speaker cord (with plug)	1 piece

