





PRESA FONO-RADIO

1280

6AQ6

50L6-GT

COMPENSATORE TONO
E INDICATORE DI LIVELLO

TESTA MAGNETICA

BOBINA D' POLARIZZAZIONE

BOBINA FONICA

300 K

4.7 M

2 M

2 M

40 μ F

G1

75 K

1 M

1 M

1 M

1 M

1 M

1 M

1 M

1 M

1 M

1 M

1 M

1 M

1 M

1 M

10'000 pF

1 M

0.1

4.7 M

330 K

420 K

150

20'000 pF

500 pF

330 K

470 K

150

20'000 pF

10'000 pF

48 Ω

4.7 K

33 Ω

33 Ω

3300 Ω

5000 pF

30 pF

50 pF

40 pF

COMMUTATORE REGISTRAZIONE - ASCOLTO
POSIZIONE ASCOLTO

TRASFORMATORE
D' USCITA

330 K Ω 470 K Ω

C1 1000 pF

C2 5000 pF

R1 82 K Ω

250 K Ω

ME OM

50L6-GT

20'000 pF

10'000 pF

48 Ω

4.7 K

OSCILLATORE
SUPERSONICO

ALTOPARL.

PRESA MICROFONO

RETE 115-125V

RETTIF.
SELENIO

