



SPECIFICATIONS

AMPLIFIER SECTION

TOTAL MUSIC POWER:	26 watts (IHF Standard at 8 ohms)
RMS POWER:	9 watts (IHF Standard at 8 ohms)
FREQUENCY RESPONSE:	20 — 60,000 Hz ± 1 dB
POWER BANDWIDTH:	30 — 25,000 Hz ± 1 dB
SIGNAL TO NOISE RATIO:	Phono — 60 dB below rated output.
INPUT SENSITIVITY:	Phono 1.5 mV, TAPE PLAY 100 mV
SPEAKER IMPEDANCE:	4 — 16 ohms
BASS CONTROL:	± 10 dB (50 Hz)
TREBLE CONTROL:	± 10 dB (10,000 Hz)
LOUDNESS CONTROL:	+10 dB (at 100 Hz), +5 dB (at 10,000 Hz)

TUNER SECTION

USABLE SENSITIVITY:	FM; 2.5 microvolts (IHF Standard) AM; 10 microvolts (IHF Standard)
FM SIGNAL TO NOISE RATIO:	63 dB (at 98 MHz)
FM IMAGE REJECTION:	50 dB
FM CAPTURE RATIO:	2.5
FM STEREO SEPARATION:	35 dB (at 400 Hz)
FM AUTOMATIC SWITCHING:	Yes
FM STEREO AUTOMATIC INDICATOR:	Yes
FM STEREO NOISE FILTER:	Yes

SPECIAL CIRCUITS:

FM Automatic, SCA Filter, FM Stereo Noise Filter, FM Stereo Automatic Indicator, Headset Jack, Tape Monitor System, Power Transistor Protection Circuit.

POWER CONSUMPTION:	50 — 60 Hz, 220 — 230 V, 45 watts
DIMENSIONS:	Width 16 1/4", Height 6", Depth 13 1/4"
NET WEIGHT:	20 lbs.



