

BOTTOM VIEW

AF C

TO IF

B+

AGC

GROUND

AM IF 455 KC
FM IF 10.7 MC

CLOCK WIRING FOR M5-6824

NOTES:
CAPACITORS—UNLESS OTHERWISE SPECIFIED,
DECIMAL VALUES IN MF, ALL OTHERS IN PF.
VOLTAGES—MEASURED FROM POINT INDICATED
TO B+ WITH A VTVM + 10% NO SIGNAL INPUT.
TUNING RANGE—AM: 535 KC TO 1620 KC. IF: 455 KC
FM: 88 MC TO 108 MC. IF: 10.7 MC

WHERE TWO VOLTAGES ARE SHOWN,
UPPER VOLTAGE IS IN FM POSITION
LOWER VOLTAGE IN AM POSITION

LEAVE CHD CAPACITY COUPLED
TO A FOR 10% APT CORR
FOR EXT APT, REMOVE COUPLED FROM A
& CORRECT 3000 EXT APT TO A & B

Q1 THRU Q10

TOP VIEW

BOTTOM VIEW

**AM IF 455 KC
FM IF 10.7 MC**

CLOCK WIRING FOR MC-1014

NOTES:
CAPACITORS—UNLESS OTHERWISE SPECIFIED,
DECIMAL VALUES IN MF; ALL OTHERS IN PF.
VOLTAGES—MEASURED FROM POINT INDICATED TO B+ WITH A VTVM + 10% NO SIGNAL INPUT.
TUNING RANGE—AM: 535 KC TO 1620 KC. IF: 455 KC.
FM: 88 MC TO 108 MC. IF: 10.7 MC.

WHERE TWO VOLTAGES ARE SHOWN,
UPPER VOLTAGE IS IN FM POSITION
LOWER VOLUME IN AM POSITION.

LIVE CHD CAPACITY COUPLED
TO A PWR SUPPLY CORD
FOR EXT. ANT., REMOVE COUPLER FROM A
& CORRECT 3000 EXT. ANT. TO A & B

SILICON

Q1 THRU Q10

BOTTOM VIEW

AM IF 455 KC
FM IF 10.7 MC

NOTES:
CAPACITORS—UNLESS OTHERWISE SPECIFIED, DECIMAL VALUES IN MF, ALL OTHERS IN PF. VOLTAGES—MEASURED FROM POINT INDICATED TO B—WITH A VTVM + 10% NO SIGNAL INPUT. TUNING RANGE—AM: 535 KC TO 1620 KC. IF: 455 KC. FM: 88 MC TO 108 MC. IF: 10.7 MC.

WHERE TWO VOLTAGES ARE SHOWN, UPPER VOLTAGE IS IN FM POSITION, LOWER VOLTAGE IN AM POSITION.

LEAVE CHD CAPACITY COUPLED TO A FOR 10% APT CORR. FOR EXT APT, REMOVE COUPLED FROM A & CORRECT 3000 EXT APT TO A & B.

Q1 THRU Q10

BOTTOM VIEW

AM IF 455 KC
FM IF 10.7 MC

NOTES:
CAPACITORS—UNLESS OTHERWISE SPECIFIED, DECIMAL VALUES IN MF, ALL OTHERS IN PF. VOLTAGES—MEASURED FROM POINT INDICATED TO B—WITH A VTVM + 10% NO SIGNAL INPUT. TUNING RANGE—AM: 535 KC TO 1620 KC. IF: 455 KC. FM: 88 MC TO 108 MC. IF: 10.7 MC.

WHERE TWO VOLTAGES ARE SHOWN, UPPER VOLTAGE IS IN FM POSITION, LOWER VOLTAGE IN AM POSITION.

LEAVE CHD CAPACITY COUPLED TO A FOR 10% APT CORR FOR EXT APT, REMOVE COUPLED FROM A & CORRECT 3000 EXT APT TO A & B.

Q1 THRU Q10

BOTTOM VIEW

TO IF

AF C

B+

AGC

GROUND

AM IF 455 KC

FM IF 10.7 MC

CLOCK WIRING FOR MS-68214

NOTES:
CAPACITORS—UNLESS OTHERWISE SPECIFIED, DECIMAL VALUES IN MF, ALL OTHERS IN PF. VOLTAGES—MEASURED FROM POINT INDICATED TO B+ WITH A VTVM + 10% NO SIGNAL INPUT. TUNING RANGE—AM: 535 KC TO 1620 KC. IF: 455 KC. FM: 88 MC TO 108 MC. IF: 10.7 MC.

WHERE TWO VOLTAGES ARE SHOWN, UPPER VOLTAGE IS IN FM POSITION, LOWER VOLTAGE IN AM POSITION.

LEAVE CHD CAPACITY COUPLED TO A FOR 10% APT CORR FOR EXT APT, REMOVE COUPLED FROM A & CORRECT 3000 EXT APT TO A & B.

1 Q1 THRU Q10

BOTTOM VIEW

TO IF

AF C

B+

AGC

GROUND

AM IF 455 KC

FM IF 10.7 MC

CLOCK WIRING FOR MS-68214

LOCATING LED

NOTES:
CAPACITORS—UNLESS OTHERWISE SPECIFIED, DECIMAL VALUES IN MF, ALL OTHERS IN PF. VOLTAGES—MEASURED FROM POINT INDICATED TO B—WITH A VTVM + 10% NO SIGNAL INPUT. TUNING RANGE—AM: 535 KC TO 1620 KC. IF: 455 KC. FM: 88 MC TO 108 MC. IF: 10.7 MC.

WHERE TWO VOLTAGES ARE SHOWN, UPPER VOLTAGE IS IN FM POSITION, LOWER VOLTAGE IN AM POSITION.

LEAVE CHD CAPACITY COUPLED TO A FOR 10% APT CORR FOR EXT APT, REMOVE COUPLED FROM A & CORRECT 3000 EXT APT TO A & B.

Q1 THRU Q10

BOTTOM VIEW

TO IF

AF C

B+

AGC

GROUND

AM IF 455 KC

FM IF 10.7 MC

CLOCK WIRING FOR MS-68214

LOCATING LED

NOTES:
CAPACITORS—UNLESS OTHERWISE SPECIFIED, DECIMAL VALUES IN MF, ALL OTHERS IN PF. VOLTAGES—MEASURED FROM POINT INDICATED TO B—WITH A VTVM + 10% NO SIGNAL INPUT. TUNING RANGE—AM: 535 KC TO 1620 KC. IF: 455 KC. FM: 88 MC TO 108 MC. IF: 10.7 MC.

WHERE TWO VOLTAGES ARE SHOWN, UPPER VOLTAGE IS IN FM POSITION, LOWER VOLTAGE IN AM POSITION.

LEAVE CHD CAPACITY COUPLED TO A FOR 10% APT CORR FOR EXT APT, REMOVE COUPLED FROM A & CORRECT 3000 EXT APT TO A & B.

1 Q1 THRU Q10

BOTTOM VIEW

TO IF

AF C

B+

AGC

GROUND

AM IF 455 KC

FM IF 10.7 MC

CLOCK WIRING FOR MS-68214

LOCATING LED

NOTES:
CAPACITORS—UNLESS OTHERWISE SPECIFIED, DECIMAL VALUES IN MF, ALL OTHERS IN PF. VOLTAGES—MEASURED FROM POINT INDICATED TO B—WITH A VTVM + 10% NO SIGNAL INPUT. TUNING RANGE—AM: 535 KC TO 1620 KC. IF: 455 KC. FM: 88 MC TO 108 MC. IF: 10.7 MC.

WHERE TWO VOLTAGES ARE SHOWN, UPPER VOLTAGE IS IN FM POSITION, LOWER VOLTAGE IN AM POSITION.

LEAVE CHD CAPACITY COUPLED TO A FOR 10% APT CORR FOR EXT APT, REMOVE COUPLED FROM A & CORRECT 3000 EXT APT TO A & B.

Q1 THRU Q10

BOTTOM VIEW

AFC B+ AGC GROUND TO IF

AM IF 455 KC
FM IF 10.7 MC

CLOCK WIRING FOR HS-6824

NOTES:
CAPACITORS—UNLESS OTHERWISE SPECIFIED,
DECIMAL VALUES IN MF; ALL OTHERS IN PF.
VOLTAGES—MEASURED FROM POINT INDICATED
TO B+ WITH A VTVM + 10% NO SIGNAL INPUT.
TUNING RANGE—AM: 535 KC TO 1620 KC. IF: 455 KC.
FM: 88 MC TO 108 MC. IF: 10.7 MC.

WHERE TWO VOLTAGES ARE SHOWN,
UPPER VOLTAGE IS IN FM POSITION;
LOWER VOLTAGE IN AM POSITION.

LEAVE CHD CAPACITY COUPLED
TO A FOR 10% APT CORR.
FOR EXT APT, REMOVE COUPLER FROM A
& CORRECT 3000 EXT APT TO A & B.

SILICON

Q1 THRU Q10

[illegible][illegible][illegible][illegible]