



PHILCO MODELS J-769 J-772 J-773 J-774 J-775 **J-838 J-840 J-842 J-845 J-846**

MODELS J-769, J-772, J-773, J-774 and J-775 have similar circuitry with slight variations as shown.

MODELS J-838, J-840, J-842, J-845 and J-846 have similar circuitry with slight variations as shown.




Dial Cord Installation—Model J 774 (Rear View)

SPEAKER PHASING, Models J-845, J-846—When replacing or connecting the two paralleled speakers, it is possible that an out of phase condition may exist; this is readily apparent by weak output and serious distortion. To correct, interchange the leads to one of the speakers.

MODELS J-774 J-775


The push button on top of the cabinet is the Forty Winks alarm control. This feature enables the user to silence the buzzer for 10 minutes. After 10 minutes the buzzer will come on again. The 10 minute cycle may be repeated indefinitely.



STEP	SIGNAL GENERATOR	RADIO			ADJUST
	CONNECTION TO RADIO	DIAL SETTING	DIAL SETTING	SPECIAL INSTRUCTIONS	
1.	Ground lead to B—; output lead through a .1 mf condenser to grid (pin 7) of 12BE6 or top of r-f tuning condenser.	455 kc.	Tuning gang fully open.	Adjust tuning cores, in order given, for maximum output.	Z2—top Z2—bottom Z1—bottom Z1—top
2.	Radiating loop (See Note below).	1620 kc.	1620 kc.	Adjust for maximum output.	C1-B—osc.
3.	Same as step 2.	1500 kc.	1500 kc.	Adjust for maximum output.	C1-A—aerial

NOTE: Make up a 6-8 turn, 6 inch diameter loop from insulated wire, connect to signal-generator leads, and place near radio loop.


PHILCO Models J-769, J-772, J-773, J-774, J-775, J-838, J-840, etc., Continued




Bottom View of Perma Circuit Panel Component Layout Model J-838

MODEL J-773

In model J-773 the silence time for the forty winks is 7 minutes. After 7 minutes the buzzer goes on again. This 7 minute cycle may be repeated 5 times.



Bottom View, Partial Printed Panel Showing Model J-769 Foil Difference in B-Circuit




Bottom View, Partial Printed Panel Showing Model J-775 Foil Difference in Rect Fil Circuit and Connections to T2

PARTS COMMON TO ALL MODELS

Sym- bol	Loca- tion	Description	Service Part No
C1	E3	Capacitor, variable, tuning	
C2	C4	Capacitor, 7.5 mmf, temp. comp.	30-1224-83
C3	H5	Capacitor, .047 mf, AVC	30-4650-45
C4	O6	Capacitor, 220 mmf, diode filter	30-1262-23
C5	J6	Capacitor, .01 mf, 1st audio grid	30-1262
C6	K5	Capacitor, .01 mf, output grid	30-1262
C7	Q4	Capacitor, 220 mmf, output grid	30-1262-23
C8	Q2	Capacitor, .01 mf, output plate	30-1262
C9	L3	Capacitor, electrolytic (3 section) 20 mf, 25 mf, 30mf, +150VDC	30-2585-11
C10	N5	Capacitor, .047 mf line bypass	30-4650-45
R1	J2	Resistor, converter grid, 22,000 ohms	66-3228340
R2	B6	Resistor, I-F bias, 68 ohms	66-0688340
R3	E6	Resistor, AVC filter, 2.2 megohms	66-5228340

Sym- bol	Loca- tion	Description	Service Part No.
R4	Q6	Resistor, volume control, .5 megohms	
R5	H6	Resistor, 1st audio grid, 10 megohms	66-6108340
R6	K5	Resistor, 1st audio plate, 470,000 ohms	66-4478340
R7	L5	Resistor, audio output grid, 470,000 ohms	66-4478340
R8	R5	Resistor, audio output bias, 150 ohms	66-1158340
R9	M3	Resistor, B+ filter, 220 ohms, 1 watt.	66-1224340
R10	L4	Resistor, B+ filter, 1000 ohms	66-2108340
R11	Q5	Resistor, isolation, 33,000 ohms	66-3338340
T1	J3	Transformer, osc.	32-4756-1
T2		Part of Speaker	32-8384-2
Z1	C2	Transformer, 1st I-F	32-4583-23
Z2	D6	Transformer, 2nd I-F	32-4583-23
G1		Contact Panel, antenna	28-12282

PHILCO Models J-769, J-772 thru J-775, J-838, J-840, J-842, etc., Continued



Bottom View of Perma Circuit Panel Component Layout Models J-772, J-773, J-774

