CUSTOMER SERVICE DEPARTMENT
COMPRESSION DRIVER TEST SPECIFICATIONS

Revision C - Effective January 16, 1984
Replaces Revision B (February 1, 1983)

MODEL	THROAT SIZE	DIAPHRAGM MATERIAL	MAGNET TYPE	NOM IMP SL	DYNAMIC TEST		DC RESISTANCE MINIMUM-MAXIMUM	NOTES
					INPUT V	SWEEP FREQ HZ		
075	Integral Horn	Aluminum	Alnico	8	7*	1K-3K	5.0 - 6.0	*Test with Network
075R	Integral Horn	Aluminum	Alnico	8	7*	1K-3K	5.0 - 6.0	*Test with Network, OEM
075-022	Integral Horn	Aluminum	Alnico	8	7*	1K-3K	5.0 - 6.0	*Test with Network, Motion Detector
075-105	Integral Horn	Aluminum	Alnico	8	7*	1K-3K	5.0 - 6.0	*Motion Detector
075-105B	Integral Horn	Aluminum	Alnico	8	7*	1K-3K	5.0 - 6.0	*Motion Detector
075-105C	Integral Horn	Aluminum	Alnico	8	7*	1K-3K	5.0 - 6.0	*Motion Detector
075-105CH	Integral Horn	Aluminum	Alnico	8	7*	1K-3K	5.0 - 6.0	*Motion Detector
075-105D	Integral Horn	Aluminum	Alnico	8	7*	1K-3K	5.0 - 6.0	*Motion Detector
076	Integral Horn	Aluminum	Alnico	16	7*	1K-3K	5.6 - 6.8	*Test with Network
077	Integral Horn	Aluminum	Alnico	16	7*	1K-3K	5.6 - 6.9	*Test with Network
LE75	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.4 - 6.6	
LE85	1-Inch	Aluminum	Alnico	16	3.5	550-1200	4.8 - 5.8	
LE100S	1-Inch	Phenolic	Alnico	16	3.5	350-1200	6.0 - 6.6	
LE175	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.4 - 6.6	
LE175-200	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.4 - 6.6	
LE175DLH	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.4 - 6.6	
LE175HP	1-Inch	Phenolic	Alnico	16	3.5	350-1200	6.0 - 6.6	

CUSTOMER SERVICE DEPARTMENT
COMPRESSION DRIVER TEST SPECIFICATIONS

Revision C - Effective January 16, 1984
Replaces Revision B (February 1, 1983)

MODEL	THROAT SIZE	DIAPHRAGM MATERIAL	MAGNET TYPE	NOM IMP SL	DYNAMIC TEST		DC RESISTANCE MINIMUM-MAXIMUM	NOTES
					INPUT V	SWEEP FREQ HZ		
D175	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.4 - 6.6	
175	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.4 - 6.6	
275	1-Inch	Aluminum	Alnico	16	3.5	550-1200	4.8 - 5.8	
375	2-Inch	Aluminum	Alnico	16	3.5	350-1200	6.4 - 7.8	
375H	2-Inch	Aluminum	Alnico	16	3.5	350-1200	6.4 - 7.8	
375AB	2-Inch	Phenolic	Alnico	16	5	350-1200	5.5 - 6.7	No Phasing Plug
375EX	2-Inch	Phenolic	Alnico	16	5	350-1200	6.0 - 6.8	No Phasing Plug
375FH	2-Inch	Phenolic	Alnico	16	5	350-1200	5.5 - 6.7	No Phasing Plug
375HP	2-Inch	Phenolic	Alnico	16	5	350-1200	5.5 - 6.7	
376	2-Inch	Aluminum	Alnico	16	3.5	350-1200	6.4 - 7.8	
2402	Integral Horn	Aluminum	Alnico	8	7*	1K-3K	5.0 - 6.0	*Test with Network
2402H	Integral Horn	Aluminum	Ferrite	8	7*	1K-3K	5.0 - 6.0	*Test with Network
2403	Integral Horn	Aluminum	Alnico	16	7*	1K-3K	5.6 - 6.9	*Test with Network
2403H	Integral Horn	Aluminum	Ferrite	16	7*	1K-3K	5.6 - 6.9	*Test with Network
2404H	Integral Horn	Aluminum	Ferrite	16	7*	1K-3K	5.6 - 6.9	*Test with Network
2404H-1	Integral Horn	Aluminum	Ferrite	8	7*	1K-3K	5.0 - 6.0	*Test with Network
2405	Integral Horn	Aluminum	Alnico	16	7*	1K-3K	5.6 - 6.9	*Test with Network
2405H	Integral Horn	Aluminum	Ferrite	16	7*	1K-3K	5.6 - 6.9	*Test with Network

CUSTOMER SERVICE DEPARTMENT
COMPRESSION DRIVER TEST SPECIFICATIONS

Revision C - Effective January 16, 1984

Replaces Revision B (February 1, 1983)

MODEL	THROAT SIZE	DIAPHRAGM MATERIAL	MAGNET TYPE	NOM IMP SL	DYNAMIC TEST		DC RESISTANCE MINIMUM-MAXIMUM	NOTES
					INPUT V	SWEEP FREQ HZ		
2410	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.4 - 6.6	
2415	1-Inch	Titanium	Ferrite	8	3	550-1200	3.5 - 4.3	Screw on mounting
2420	1-Inch	Aluminum	Alnico	16	3.5	550-1200	4.8 - 5.8	
2421A	1-Inch	Aluminum	Alnico	8	2.85	550-1200	3.6 - 4.4	
2421B	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.7 - 6.9	
2425H	1-Inch	Titanium	Ferrite	8	2.85	550-1200	3.6 - 4.4	
2425J	1-Inch	Titanium	Ferrite	16	3.5	550-1200	5.7 - 6.9	
2440	2-Inch	Aluminum	Alnico	16	3.5	350-1200	6.4 - 7.8	
2441	2-Inch	Aluminum	Alnico	16	3.5	350-1200	6.4 - 7.8	
2445J	2-Inch	Titanium	Ferrite	16	3.5	350-1200	6.4 - 7.8	
2460	1-Inch	Phenolic	Alnico	16	3.5	350-1200	6.0 - 6.6	
2461	1-Inch	Phenolic	Alnico	16	5	350-1200	9.2 -11.2	
2470	1-Inch	Phenolic	Alnico	16	5	350-1200	9.9 -12.1	
2480	2-Inch	Phenolic	Alnico	16	3.5	350-1200	5.5 - 6.7	
2482	2-Inch	Phenolic	Alnico	16	5	350-1200	8.6 - 9.5	
HL180	1-Inch	Phenolic	Alnico	16	5	350-1200	9.9 -12.1	
5A 350	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.4 - 6.6	OEM
5P 350	1-Inch	Phenolic	Alnico	16	3.5	350-1200	6.0 - 6.6	OEM

CUSTOMER SERVICE DEPARTMENT
COMPRESSION DRIVER TEST SPECIFICATIONS

Revision C - Effective January 16, 1984
Replaces Revision B (February 1, 1983)

MODEL	THROAT SIZE	DIAPHRAGM MATERIAL	MAGNET TYPE	NOM IMP SL	DYNAMIC TEST		DC RESISTANCE MINIMUM-MAXIMUM	NOTES
					INPUT V	SWEEP FREQ HZ		
5A 355	1-Inch	Aluminum	Alnico	16	3.5	550-1200	4.8 - 5.8	OEM
5P 355	1-Inch	Phenolic	Alnico	16	5	350-1200	9.9 -12.1	OEM
5A 360	2-Inch	Aluminum	Alnico	16	3.5	350-1200	6.4 - 7.8	OEM
5P 360	2-Inch	Phenolic	Alnico	16	5	350-1200	5.5 - 6.7	OEM
MI 11419	1-Inch	Aluminum	Alnico	16	3.5	550-1200	5.4 - 6.6	OEM
MI 11426	2-Inch	Phenolic	Alnico	16	5	350-1200	5.5 - 6.7	OEM
MI 11426A	2-Inch	Phenolic	Alnico	16	5	350-1200	5.5 - 6.7	OEM
MI 11427	2-Inch	Aluminum	Alnico	16	3.5	350-1200	6.4 - 7.8	OEM